

CP2-LTE

HD Video Telematics Camera
Real-time Location and Video
Transfer



This is Video Telematics



Back: Driver-facing



Front: Road-facing

Introducing the **CP2-NA-LTE**, the world's most advanced incident camera with 1080p HD video, built-in WiFi, bluetooth 4.2 and LTE, live GPS position and driver behavior reports to support post incident analysis. The **CP2-NA-LTE** will record exactly what happened before, during and after an incident. It will record the driver's view of the road, vehicle location, impact force, audio, speed, acceleration, braking and steering. We recommended a second camera for recording driver and interior views.

Features:

- 1080P HD video with 150° wide angle lens
- Up to 128 GB SD storage
- Video sent in real-time via email or to your telematics software
- Up to 166 hours of local storage
- Instant notification of events & live GPS location tracking
- Tamper-resistant design
- Built-in WiFi, Bluetooth 4.2 and LTE

Driver Protection Against:

- Staged Accidents
- False and/or Exaggerated Claims
- Conflicting Reports of Incidents
- Driving allegations (speeding, traffic signal violation, swerving, etc.)

SPECIFICATIONS

| | |
|-------------------------|--|
| Image Sensor | 2 Megapixel CMOS sensor |
| Angle of View | 150 °(H : 121.1°, V : 62.4 ± 5%) |
| Wireless | [CAT1] B2(1900),B4(AWS),B5(850),B12(700AC) B13(700C); [3G] B2(1900),B5(850) (802.11 b/g/n) and Bluetooth (4.2) |
| Max Data Rate | UL: 5Mbps, DL: 10Mbps |
| Video Resolution | 1080p(1920x1080) 720p(1280x720) VGA(640x480) 2nd camera: D1(720x480) |
| Recording Speed | CH1: FHD (30 fps) CH1 + CH2: FHD (15 fps) + D1 (30 fps) |
| Recording Mode | Continuous, Event and Dual Mode |
| Memory | Supports SD cards up to 128 GB (FAT32) |
| GPS / GLONASS | INTERNAL GPS / GLONASS |
| G-Sensor | Internal 3- axis G-Sensor |
| Gyro | 3 Axis (X,Y,Z), output rate: 100 Hz |
| RTC | Internal super capacitors |
| Speaker | Recording start error |
| Audio | Internal Microphone |
| Alarm In / Out | 2 x Alarm In 1x Alarm Out |
| LED | 3 (Red, Blue, Green LED) |
| Super Capacitor | Enables recording of last file & safe shutdown |
| PC Software | Included |
| Power Input | 12 to 24 Volt DC permanent wiring kit Input Voltage: DC 5 V, 3 A |
| Power Consumption | 15 Watt |
| Delayed Power Shutdown | Supports delayed power shutdown |
| Size / Weight | 164mm x 640 (w/o brackets) 180g (w/o cable) |
| Operational Temperature | -10° C ~ 85° C |